


Durch den Einbau von **TRIMEX® -Einzel Schubdornen** können Dehnfugen mit unterschiedlich großen zu übertragenden Kräften einfach und sicher verdübelt werden. Der TRIMEX®-Dorn muss von der Fugenkante mindestens 13 cm im Beton eingespannt sein.

- Dehnfugenverdübelung von Betonplatten
- Dehnfugenverdübelung bei Parkdecks / Tiefgaragen
- Scheinfugenausbildungen bei Betonfahrbahnen
- Anschlüsse von Stützwänden bei glatten, verdübelten Pressfugen
- Fixieren von nichttragenden Trennwänden unter Decken und Riegeln

By installing **TRIMEX® single shear dowels**, expansion joints with expansion joints with different sizes of forces to be transmitted can be doweled easily and safely. The TRIMEX® dowel must be clamped in the concrete at least be clamped in the concrete for at least 13 cm.

- Expansion joint dowelling of concrete slabs
- Expansion joint dowelling for parking decks / underground garages
- Dummy joint formations for concrete roadways
- Connections of stud walls with smooth, doweled compression joints
- Fixing of non-bearing partition walls underneath ceilings and transoms




Rundhülse PVC:

ab Lager DE

Round sleeve PVC

ex stock Germany




Rundhülse Edelstahl A2:

ab Lager CH

Round sleeve stainless steel A2:

ex stock Switzerland




Rechteckhülse Edelstahl:

ab Lager CH

Rectangular sleeve stainless steel:

ex stock Switzerland



Ovalhülse PVC:

ab Lager CH

Oval sleeve PVC:

ex stock Switzerland

Innendurchmesser 20.1 mm

Längen 160 mm, 180 mm, 210 mm

txr20160-k, txr20180-k, txr20210-k

Inner diameter 20.1 mm

Lengths 160 mm, 180 mm, 210 mm

txr20160-k, txr20180-k, txr20210-k



Innendurchmesser 20.1 mm

Längen 160 mm, 180 mm, 210 mm

txr20160-2, txr20180-2, txr20210-2

Inner diameter 20.1 mm

Lengths 160 mm, 180 mm, 210 mm

txr20160-2, txr20180-2, txr20210-2



Innendurchmesser 20.0 mm


Längen 160 mm, 180 mm, 210 mm

txq20160-2, txq20180-2, txq20210-2

Inner diameter 20.0 mm

Lengths 160 mm, 180 mm, 210 mm

txq20160-2, txq20180-2, txq20210-2



Innendurchmesser 20.0 mm

Längen 100 mm

txo2147100-k

Inner diameter 20.0 mm

Lengths 100 mm

txo2147100-k



Typ / Type	Material / Material	Durchmesser / Diameter	Länge / Length	
txd20300-v	verzinkt / galvanized	20 mm	300 mm	Stahl CK 60 / steel CK 60
txd20300-6	Edelstahl hochfest / stainless steel inox	20 mm	300 mm	Fließgrenze mind. - fy 700 N/mm ² / Flow limit min. - fy 700 N/mm ²